



32" Open Frame Touch Monitor

artistry in technology



MAIN SPECIFICATIONS

U41-OF320

LCD Panel	32" TFT Rear Mount Touch Monitor
Case/Bezel Colour	Black
Touch Monitor Performance	Standard
Display Type	16:9 Ratio 32" Active Matrix TFT LCD
Active Display Area	697.68 x 392.26 mm
Native Resolution	1366 x 768 @ 60 Hz
Synchronization Range	48 Khz Horizontal, 60 Hz Vertical
Pixel Response Time	16 ms
Plug and Play	VESA DDC 1/2B
On Screen Display (OSD)	Remote OSD with 1.2 m cable
Colours	16.7 Million
Brightness	500 cd/m ²
Contrast Ratio	1200:1
Viewing Angle Horizontal (Left/Right)	178° (89°/89°)
From Centre, CR>=10 Vertical (Up/Down)	178° (89°/89°)
Backlight Lamp Life	50,000
Input Video Format	Analog VGA and DVI
Touch Technology	Surface Acoustic Wave (SAW)
Touchscreen Interface	Serial (RS232) or USB
Touch Response Time	10.4 ms
Touch Sensitivity	Fixed
Monitor Dimensions	784 x 474 x 102 mm
Shipping Carton Dimensions	925 x 615 x 240 mm
Weight (approximately) Monitor/Shipping	17 Kg/20 Kg
Mounting Options	Rear Mount, VESA 75 & 100mm Included
Power Supply	External: 100-240V, 50-60Hz
Power Consumption	124 W max
Temperature Range	Operating: 0 °C - 50 °C, Storage: -20 °C - 60 °C
Relative Humidity (Non Condensing)	Operating: 10% - 90%, Storage: 5% - 90%
Warranty	1 Year
Agency Approvals	FCC, CE, ETL, RoHS

FEATURES

- High class LCD panel with wide viewing angle
- Fast touch response time
- USB touch interface
- VESA mount
- On screen display

TOUCH PART NUMBERS

Non Touch	U41-OF320
SAW	U41-OF320US

APPLICATIONS:

- Digital Signage
- Point of Information (POI)
- Museums
- Hospitality

Visit us:
www.unytouch.ca
sales@unytouch.ca

Unytouch Manufacturing, Inc.

27 Armthorpe Road
 Brampton, Ontario, L6T 5M4
 Phone: (905) 792-0542
 Toll Free: (800) 260 6249
 Fax: (905) 792-2843