

# 19" Rear Mount Touch Monitor

artistry in technology



REAR VIEW



SIDE VIEW



- VESA Mount
- Adjustable Mounting Brackets
- Replacement for ELO1939L



## MAIN SPECIFICATIONS U41-RM190US

LCD Panel	19" TFT Active Matrix LCD Display
Resolution	1280 x 1024 Pixels, 16.7M Colors
Contrast Ratio	700:1
Brightness	300 cd/m <sup>2</sup>
Response Time	8 ms
Pixel Pitch	0.294 mm x 0.294 mm
Plug & Play	DDC 2B Compliance
OSD (On Screen Display)	Auto Tune, Brightness, Contrast, Clock, Phase, H-position, V-position, Recall
Touch Technology	SAW
Touch Interface	USB, Serial
Touch Active Area (W/H)	376 mm x 301 mm
Operating Environment	0°C - 50 °C (32°F - 122°F) 10% - 80% (no condensation)
Storage Conditions	-20°C - 60°C (-4°F - 140°F) 10% - 90% (no condensation)
Product Dimensions (W/H/D) mm	425.7 x 353.7 x 53
Package Dimensions (W/H/D) mm	530 x 460 x 200
Weight Gross	7 Kgs
Monitor Tilting Degree	Fixed
Color	Grey
Viewing Angle	70°/70°/70°/60°(L/R/U/D)
MTBF	50,000 Hours
PC Video Interface	Analog RGB (VGA)
Horizontal Scan Rate (Khz)	30-80 Khz
Vertical Scan Rate (Hz)	60-75 Hz
Display Mode	VGA 720 x 400 (70 Hz) VGA 640 x 480 (60/66/70/72/75 Hz) SVGA 800 x 600 (60/70/72/75 Hz) XGA 1024 x 768 (56/70/75 Hz) SXGA 1280 x 1024 (60, 70, 72, 80 Hz)
Electrical Power	Adapter Input 100-240 VAC, 50-60 Hz 1.5A
Power Consumption	50W (Max)
Certification	FCC, CE, ETL, ROHS

Visit us:  
[www.unytouch.ca](http://www.unytouch.ca)  
sales@unytouch.ca

APPLICATIONS:  
- Industrial  
- Gaming  
- Custom or OEM Applications

**Unytouch Manufacturing, Inc.**

27 Armthorpe Road  
Brampton, Ontario, L6T 5M4  
Phone: (905) 792-0542  
Toll Free: (800) 260 6249  
Fax: (905) 792-2843